

Appl. No. 09/751,332
Amdt. Dated September 13, 2007

Appendix

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-36. (Cancelled).

37. (Previously Presented) A method of automatically adjusting a fragmentation threshold for data transmissions between an access point and one or more associated wireless units, comprising:

determining a transmission error factor indicative of errors occurring in a transmission of one or more data packets between the access point and the one or more associated wireless units; and

automatically adjusting the fragmentation threshold based on the transmission error factor by changing the fragmentation threshold by a divisional factor each time the fragmentation threshold is adjusted, the fragmentation threshold being based on a pre-determined fragmentation threshold divided by the divisional factor.

38. (Previously Presented) The method of claim 37, wherein the determining of the transmission error factor comprises:

transmitting the one or more data packets; and

determining the transmission error factor based on a number of acknowledgement packets received in response to the transmitted one or more data packets.

39. (Previously Presented) The method of claim 37, wherein the transmission error factor is based on a number of errors occurring in the transmission of the one or more data packets.

40. (Previously Presented) The method of claim 37, wherein the transmission error factor is a value based on (i) a number of transmission errors occurring successively multiplied

Appl. No. 09/751,332
Amdt. Dated September 13, 2007

by a first weighting factor and (ii) a number of transmission errors occurring sporadically multiplied by a second weighting factor, the first weighting factor being greater than the second weighting factor.

41-45. (Cancelled).

46. (Previously Presented) The method of claim 37, wherein the pre-determined fragmentation threshold is a maximum data packet size for transmission over a backbone network of a wireless network formed by the access point and the one or more associated wireless units.

47. (Previously Presented) The method of claim 46, wherein the pre-determined fragmentation threshold is related to a maximum data packet size for transmission over a wireless medium operating as a wireless communication path between the access point and the one or more associated wireless units.

48. (Currently Amended) Adapted to communicate with one or more associated wireless units, an access point comprising:

an address table; and

a logic circuit in communication with the address table, the logic circuit to:

determine a transmission error factor indicative of errors occurring in a transmission of a first group of data packets to the one or more associated wireless units, the transmission error factor being a weighted value with transmission errors occurring successively having a different weighting than transmission errors experienced by the first group of data packets occurring sporadically; and

automatically adjust the fragmentation threshold based on the transmission error factor after translating a desired finite time duration for the transmission into the fragmentation threshold based on a data transmission rate of a second group of data packets following the first group of data packets, the fragmentation threshold is based on a pre-determined fragmentation

Appl. No. 09/751,332
Amdt. Dated September 13, 2007

threshold divided by a divisional factor and is adjusted by the divisional factor each time the fragmentation threshold is adjusted.

49. (Previously Presented) The access point of claim 48, wherein the logic circuit in determining the transmission error factor is capable of:

transmitting the first group of data packets to the one or more associated wireless units;
and

determining the transmission error factor based on a number of acknowledgement packets received in response to the transmitted the first group of data packets from the one or more associated wireless units.

50. (Previously Presented) The access point of claim 48, wherein the transmission error factor depends on a number of errors occurring in the transmission of the first group of data packets.

51. (Previously Presented) The access point of claim 48, wherein the transmission error factor is a value based on (i) a number of transmission errors occurring successively for the first group of data packets multiplied by a first weighting factor and (ii) a number of transmission errors occurring sporadically for the first group of data packets multiplied by a second weighting factor.

52. (Previously Presented) The access point of claim 48, wherein the transmission error factor is a weighted value with the transmission errors occurring successively having a greater weighting than transmission errors experienced by the first group of data packets occurring sporadically.

53. (Previously Presented) The access point of claim 48, wherein the logic circuit in automatically adjusting the fragmentation threshold is capable of:

comparing the transmission error factor to an upper threshold; and

Appl. No. 09/751,332
Amdt. Dated September 13, 2007

decreasing the finite time duration by decreasing the fragmentation threshold if the transmission error factor is above the upper threshold.

54. (Previously Presented) The access point of claim 48, wherein the logic circuit in automatically adjusting the fragmentation threshold is capable of:

comparing the transmission error factor to a lower threshold; and

increasing the finite time duration by increasing the fragmentation threshold if the transmission error factor is below the lower threshold.

55. (Cancelled).

56. (Previously Presented) The access point of claim 48, wherein the pre-determined fragmentation threshold is a maximum data packet size for transmission over a backbone network of a wireless network formed by the access point and the one or more associated wireless units.

57. (Previously Presented) A method of automatically adjusting a fragmentation threshold for data transmissions between an access point and at least one wireless unit, comprising:

determining a transmission error factor indicative of errors occurring in a transmission of one or more data packets between the access point and the at least one wireless unit, the transmission error factor being a weighted value with transmission errors occurring successively having a different weighting than transmission errors experienced by a first group of data packets occurring sporadically; and

adjusting the fragmentation threshold based on the transmission error factor after translating a desired finite time duration for the transmission into the fragmentation threshold based on a transmission rate of at least one data packet following the one or more data packets, the fragmentation threshold is a pre-determined fragmentation threshold divided by a divisional factor and is adjusted by the divisional factor each time the fragmentation threshold is adjusted.

Appl. No. 09/751,332
Amdt. Dated September 13, 2007

58. (Previously Presented) The method of claim 57, wherein the determining of the transmission error factor comprises:

transmitting the one or more data packets; and
determining the transmission error factor based on a number of acknowledgement packets received in response to the transmitted one or more data packets.

59. (Previously Presented) The method of claim 57, wherein the transmission error factor is based on a number of errors occurring in the transmission of the one or more data packets.

60. (Previously Presented) The method of claim 57, wherein the transmission error factor is a value based on (i) a number of transmission errors occurring successively multiplied by a first weighting factor and (ii) a number of transmission errors occurring sporadically multiplied by a second weighting factor, the first weighting factor being greater than the second weighting factor.

61. (Previously Presented) The method of claim 57, wherein the transmission error factor is a weighted value with transmission errors occurring successively to each other having a greater weighting than transmission errors occurring sporadically.

62. (Previously Presented) The method of claim 57, wherein automatically adjusting the fragmentation threshold comprises:
comparing the transmission error factor to an upper threshold; and
decreasing the finite time duration by decreasing the fragmentation threshold if the transmission error factor is above the upper threshold.

63. (Previously Presented) The method of claim 57, wherein automatically adjusting the fragmentation threshold comprises:
comparing the transmission error factor to a lower threshold; and

Appl. No. 09/751,332
Amdt. Dated September 13, 2007

increasing the finite time duration by increasing the fragmentation threshold if the transmission error factor is below the lower threshold.

64. (Cancelled).

65. (Previously Presented) The method of claim 57, wherein the pre-determined fragmentation threshold is a maximum data packet size for transmission over a backbone network of a wireless network formed by the access point and the one or more wireless units.

66. (Cancelled).

67. (Currently Amended) An access point, adapted to communicate with at least one wireless unit via a wireless medium to provide the at least one wireless unit access to a wireless network, comprising:

a wireless transceiver; and

a logic circuit coupled to the wireless transceiver. the logic unit to (i) determine a transmission error factor indicative of errors occurring in a transmission of one or more data packets between the access point and the at least one wireless unit, the transmission error factor being a weighted value with transmission errors occurring successively having a different weighting than transmission errors experienced by a first group of data packets occurring sporadically, and (ii) adjust the fragmentation threshold based on the transmission error factor after translating a desired finite time duration for the transmission into the fragmentation threshold based of a transmission rate of at least one data packet following the one or more data packets, the fragmentation threshold, being based on a pre-determined fragmentation threshold divided by a divisional factor, is adjusted by changing the divisional factor each time the fragmentation threshold is adjusted.

68. (Previously Presented) The access point of claim 67, wherein the logic circuit to determine the transmission error factor by computing a weighted value with transmission errors

Appl. No. 09/751,332
Amdt. Dated September 13, 2007

occurring successively having a greater weighting than transmission errors experienced by the one or more packets occurring sporadically.

69. (Cancelled).